










Type:

**SPECIFICATION SHEET** 

Project: Page 1 / 5

# **VEGA**-Premium

# **TVM20P-11**



#### **DESCRIPTION**

This high-efficacy track light boasts an impressive 125lm/w, combining compact design with a slim, sleek aesthetic. Its superior light distribution fits seamlessly into retail and commercial settings. Equipped with a wide range of optical accessories, this model offers easy replacement and flexible adjustments to meet any lighting need.

#### **FEATURES**

- Slim and sleek aesthetic design without screw.
- High power in compact size (Ultra mini size 1.5"/40mm dia).
- High efficacy 125lm/W.
- High CRI 95 for vivid colors, COB SDCM≤2 for high consistency.
- Tunable white 2700-6500K optional.
- In-track driver for flexible dimming: triac, dali, wireless control.
- Wide range of Interchangeable accessories: honey-comb, soft, oval filter etc.
- Flexible mounting options: Track-mounted, Surface-mounted.
- 360+° rotatable, 90° tiltable.

## **ELECTRICAL**

20W Power: Voltage: 230V AC 50/60Hz Frequency: Power factor:

On-off / 1-10V / DALI / TRIAC / CASAMBI Dimming:

#### **OPTICAL**

LED type: СОВ Lumen output: 2528lm 30° / 40° / 52° Beam optic: Color quality: CRI 90+, SDCM≤2

Light color: Static white: 2700K/3000K/3500K/4000K

Tunable white: 2700K-6500K


#### **LUMINAIRE**

Installation methods: Track-mounted / Surface-mounted

Black / White / Silver Housing color:

Operating temperature: -20°C~40°C >50000h@80%(L80) Lifespan: Warranty: 5 years limited warranty

# **DETAILS**







$\in$	<u></u> TÜV	









Project:

**SPECIFICATION SHEET** 

Page 2 / 5

## **ORDERING INFORMATION**

TVM	-	-		-				
SERIES	POWER	INSTALLATION	HOUSING COLOR	TRACK TYPE	CRI	сст	OPTIC	DIMMING
TVM VEGA Φ60mm	20P 20W Premium Version	Track  12 Surface	W White  B Black  S Silver	02 2-pin  03 3-pin  41 4-pin  63 6-pin	□ 8 80+ □ 9 90+	27 2700K  30 3000K  35 3500K  40 4000K  TW Tunable White 2700K-6500K	□ 030 30° □ 040 40° □ 052 52°	V 1-10V  Triac  X 0-10V/Triac  DD DALI  CCASAMBI  Non-dimming

ACCESSORIES (TO BE ORDERED SEP ARATELY) FOR INSTALLATION CONSULT THE INSTRUCTION SHEET

OPTICAL ACCESSOR	Y		
Honeycomb TVM20P-H	Oval Lens TVM20P-OV	Polarized Lens TVM20P-PL	Soft Lens TVM20P-SL









POWER	сст	CRI	BEAM OPTIC	LUMENS (lm)	EFFICACY (lm/W)	MAX CANDELA (cd)
			30°	2405	114	6381
20W	3000K	90	40°	2478	118	5807
			52°	2528	120	3457


Type:

# LIGHT DISTRIBUTION

# 3000K 20W







#### **LUMEN MULTIPLIERS**

ССТ	MULTIPLIER
2700K	0.91
3000K	1.00
3500K	1.01
4000K	1.02

# **Applying Lumen Multipliers to Calculate Deliveried Lumens**

Base Fixture Delivered Lumen (from PHOTOMETRIC DAT	- Y	CCT Multiplier	=	Delivered Lumens for Desired Fixture			
PREMIUM TRIM Example: TVM20P 20W 3500K							
2528 lm	×	1.01	=	2553.28 lm			

















## **DIMENSION**









Project:



**INSTALLATION** 


Track-mounted

















## Surface-mounted





Project: Page 5 / 5













## **VEGA TRACK LIGHT SYSTEM**

The VEGA track light series is a versatile lighting collection that includes standard, premium, zoomable, and framing options, designed to function as a complete lighting system.

With its slim and sleek appearance, this series not only enhances the aesthetics of any space but also provides museum-quality illumination with precise control. Its modular design supports a broad array of optical accessories and mounting options, positioning Vega as the optimal solution for retail environments, commercial spaces, museums, and galleries

# **DETAILS**



Scan to know more about product information

