



VEGA-Premium

TVL30P-11



DESCRIPTION

This high-efficacy track light boasts an impressive 125lm/w, combining compact design with a slim, sleek aesthetic. Its superior light distribution fits seamlessly into retail and commercial settings. Equipped with a wide range of optical accessories, this model offers easy replacement and flexible adjustments to meet any lighting need.

FEATURES

- Slim and sleek aesthetic design without screw.
- High power in compact size (Ultra mini size 1.5"/40mm dia).
- High efficacy 125lm/W.
- High CRI 95 for vivid colors, COB SDCM≤2 for high consistency.
- Tunable white 2700-6500K optional.
- In-track driver for flexible dimming: triac, dali, wireless control.
- Wide range of Interchangeable accessories: honey-comb, soft, oval filter etc.
- Flexible mounting options: Track-mounted, Surface-mounted.
- 360+° rotatable, 90° tiltable.

ELECTRICAL

Power:	30W
Voltage:	230V AC
Frequency:	50/60Hz
Power factor:	>0.90
Dimming:	On-off / 1-10V / DALI / TRIAC / CASAMBI


OPTICAL

LED type:	COB
Lumen output:	3861lm
Beam optic:	24° / 30° / 40° / 52°
Color quality:	CRI 90+, SDCM≤2
Light color:	Static white: 2700K/3000K/3500K/4000K Tunable white: 2700K-6500K

LUMINAIRE

Installation methods:	Track-mounted / Surface-mounted
Housing color:	Black / White / Silver
Operating temperature:	-20°C~40°C
Lifespan:	>50000h@80%(L80)
Warranty:	5 years limited warranty

DETAILS





ORDERING INFORMATION

TVL								
SERIES	POWER	INSTALLATION	HOUSING COLOR	TRACK TYPE	CRI	CCT	OPTIC	DIMMING
☐ TVL VEGA Φ83mm	☐ 30P 30W Premium Version	☐ 11 Track ☐ 12 Surface	☐ W White ☐ B Black ☐ S Silver	☐ 02 2-pin ☐ 03 3-pin ☐ 41 4-pin ☐ 63 6-pin	☐ 8 80+ ☐ 9 90+	☐ 27 2700K ☐ 30 3000K ☐ 35 3500K ☐ 40 4000K ☐ TW Tunable White 2700K-6500K	☐ 024 24° ☐ 030 30° ☐ 040 40° ☐ 052 52°	☐ V 1-10V ☐ T Triac ☐ X 0-10V/Triac ☐ D DALI ☐ C CASAMBI ☐ N Non-dimming

ACCESSORIES (TO BE ORDERED SEPARATELY)
FOR INSTALLATION CONSULT THE INSTRUCTION SHEET

OPTICAL ACCESSORY

☐ Honeycomb
TVL30P-H


☐ Oval Filter
TVL30P-OV


☐ Polarized Lens
TVL30P-PL


☐ Soft Lens
TVL30P-SL





PHOTOMETRIC DATA (NON-DIMMING)

POWER	CCT	CRI	BEAM OPTIC	LUMENS (lm)	EFFICACY (lm/W)	MAX CANDELA (cd)
30W	3000K	90	24°	3809	124	17855
			30°	3828	125	13150
			40°	3861	126	7234
			52°	3679	120	4642

LIGHT DISTRIBUTION

3000K 30W




LUMEN MULTIPLIERS

CCT	MULTIPLIER
2700K	0.91
3000K	1.00
3500K	1.01
4000K	1.02

Applying Lumen Multipliers to Calculate Delivered Lumens


Base Fixture Delivered Lumens (from PHOTOMETRIC DATA)	x	CCT Multiplier	=	Delivered Lumens for Desired Fixture
PREMIUM TRIM Example: TVL30P 30W 3500K				
3809 lm	x	1.01	=	3847 lm

DIMENSION



INSTALLATION

Track-mounted



Surface-mounted





VEGA TRACK LIGHT SYSTEM

The VEGA track light series is a versatile lighting collection that includes standard, premium, zoomable, and framing options, designed to function as a complete lighting system.

With its slim and sleek appearance, this series not only enhances the aesthetics of any space but also provides museum-quality illumination with precise control. Its modular design supports a broad array of optical accessories and mounting options, positioning Vega as the optimal solution for retail environments, commercial spaces, museums, and galleries.

DETAILS



Scan to know more about product information