



Type:

**SPECIFICATION SHEET**

Project:

Page 1 / 5

# OVEGA-Zoomable

TLO020-31 / TLO025-31 / TLO030-31



## DESCRIPTION

OVEGA(EN-TLO series, Zoomable version) is a stylish and compact LED track light that will fit smoothly into any museum, gallery and retail environments. Featuring an adjustable beam mechanism designed to provide endless beam options from a 10° narrow to a 60° wide flood distribution. The head can be adjusted precisely 360°+ horizontal(rotation) and 90° vertical without dead angle. The light, as a result, is emitted exactly where you need it. The integrated driver gives clean feeling and the ceiling will not be cluttered with drivers aimed in different directions.

## FEATURES

- Stylish and compact design with integrated driver.
- Excellent modular combination concept: integrated driver+ different fixture bases, DIY to get different light solutions and easy for maintenance.
- Beam angle adjustable mechanism provides endless beam options from a narrow to wide flood distribution by simply rotate the rubber ring.
- Light efficiency is up to 90lm/W.
- Patented joints can hold the track head at any positions without malfunctions.
- 360°+ rotation without dead angle and 90° vertical aiming.
- Use OVEGA family to get a unified impression in one environment.

## ELECTRICAL

Power: 20W / 25W / 30W  
 Voltage: 220-240V / 100-277V AC  
 Frequency: 50/60Hz  
 Class: II  
 Power Factor: >0.90  
 Dimming: On-off / 0/1-10V / DALI / TRIAC


## OPTICAL

LED Type: COB  
 Lumen Output: 1789lm(20W), 2107lm(25W),2463lm(30W)  
 Beam Optic: 10°-60°(20W/25W), 25°-60°  
 Color Quality: CRI 80+/90+/95+, SDCM≤3  
 Color Temperature: Static white: 2700K/3000K/3500K/4000K  
 TM30 values: Rf: 99-105 Rg: 88-92  
 LM80: ANSI/IES LM-80-15

## LUMINAIRE

Location: Indoor  
 Installation Methods: Track-mounted / Surface-mounted / Pendant / Wall-mounted  
 IP Rating: IP20  
 Adjustability: 0°-90° tiltable, 360°+ rotatable  
 Luminaire Color: RAL9005 Black / RAL9016 White / Custom Finish\*(Consult Factory)  
 Material: Die-cast aluminum  
 Operating Temperature: -20°C~40°C  
 Lifespan: > 50000h@80%(L80)  
 Warranty: 5 years Carefree for Parts and Components (Labor not included) LED luminaire life reduction and warranty invalidation will occur if installed in environments above 40°C

## DETAILS



**ORDERING INFORMATION**

| TLO                                          |                                            |                                               |                                                                          |                                                       |                                          |                                             |                                                                  |                                                  |
|----------------------------------------------|--------------------------------------------|-----------------------------------------------|--------------------------------------------------------------------------|-------------------------------------------------------|------------------------------------------|---------------------------------------------|------------------------------------------------------------------|--------------------------------------------------|
| SERIES                                       | POWER                                      | INSTALLATION                                  | HOUSING COLOR                                                            | TRACK TYPE                                            | CRI                                      | CCT                                         | OPTIC                                                            | DIMMING                                          |
| <input type="checkbox"/> <b>TLO</b><br>OVEGA | <input type="checkbox"/> <b>020</b><br>20W | <input type="checkbox"/> <b>31</b><br>Track   | <input type="checkbox"/> <b>W</b><br>RAL9016<br>White                    | <input type="checkbox"/> <b>J</b><br>2-pin Juno       | <input type="checkbox"/> <b>8</b><br>80+ | <input type="checkbox"/> <b>27</b><br>2700K | <b>20W-25W</b><br><input type="checkbox"/> <b>1T6</b><br>10°-60° | <input type="checkbox"/> <b>V</b><br>0/1-10V     |
|                                              | <input type="checkbox"/> <b>025</b><br>25W | <input type="checkbox"/> <b>32</b><br>Surface | <input type="checkbox"/> <b>B</b><br>RAL9005<br>Black                    | <input type="checkbox"/> <b>L</b><br>2-pin Lightolier | <input type="checkbox"/> <b>9</b><br>90+ | <input type="checkbox"/> <b>30</b><br>3000K | <b>20W-30W</b><br><input type="checkbox"/> <b>2T6</b><br>25°-60° | <input type="checkbox"/> <b>T</b><br>Triac       |
|                                              | <input type="checkbox"/> <b>030</b><br>30W | <input type="checkbox"/> <b>33</b><br>Pendant | <input type="checkbox"/> <b>C</b><br>Custom Finish<br>*(Consult Factory) | <input type="checkbox"/> <b>H</b><br>3-pin Halo       | <input type="checkbox"/> <b>H</b><br>95+ | <input type="checkbox"/> <b>35</b><br>3500K |                                                                  | <input type="checkbox"/> <b>X</b><br>0-10V/Triac |
|                                              |                                            | <input type="checkbox"/> <b>34</b><br>Wall    |                                                                          | <input type="checkbox"/> <b>G</b><br>4-pin Global     |                                          | <input type="checkbox"/> <b>40</b><br>4000K |                                                                  | <input type="checkbox"/> <b>D</b><br>DALI        |
|                                              |                                            |                                               |                                                                          | <input type="checkbox"/> <b>D</b><br>6-pin DALI       |                                          |                                             |                                                                  | <input type="checkbox"/> <b>N</b><br>Non-dimming |

**ACCESSORIES** (TO BE ORDERED SEPARATELY)  
FOR INSTALLATION CONSULT THE INSTRUCTION SHEET

**OPTICAL ACCESSORY**

|                                                                                                                                              |                                                                                                                                                   |                                                                                                                                                 |                                                                                                                                           |                                                                                                                                                  |                                                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> <b>Honeycomb</b><br>TLO-AC11<br> | <input type="checkbox"/> <b>Circular Small</b><br>TLO-AC24<br> | <input type="checkbox"/> <b>Circular Big</b><br>TLO-AC25<br> | <input type="checkbox"/> <b>Square</b><br>TLO-AC26<br> | <input type="checkbox"/> <b>Rectangular</b><br>TLO-AC27<br> | <input type="checkbox"/> <b>Wall Washing</b><br>TLO-AC28<br> |
|----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|



Type:

**SPECIFICATION SHEET**

Project:

Page 3 / 5

**PHOTOMETRIC DATA (NON-DIMMING)**

| LUMEN PACKAGE | POWER | CCT   | 10°    |          |             | 60°    |          |             | 25°    |          |             | 60°    |          |             |
|---------------|-------|-------|--------|----------|-------------|--------|----------|-------------|--------|----------|-------------|--------|----------|-------------|
|               |       |       | LUMENS | EFFICACY | MAX CANDELA |
| TLO020-31     | 20W   | 3000K | 1090   | 52       | 22506       | 1366   | 65       | 1783        | 1628   | 88       | 8405        | 1789   | 97       | 1918        |
| TLO025-31     | 25W   | 3000K | 1232   | 47       | 25733       | 1484   | 57       | 1927        | 1920   | 85       | 9908        | 2107   | 93       | 2258        |

| LUMEN PACKAGE | POWER | CCT   | 25°    |          |             | 60°    |          |             |
|---------------|-------|-------|--------|----------|-------------|--------|----------|-------------|
|               |       |       | LUMENS | EFFICACY | MAX CANDELA | LUMENS | EFFICACY | MAX CANDELA |
| TLO030-31     | 30W   | 3000K | 2244   | 84       | 11612       | 2463   | 92       | 2638        |

**LUMEN MULTIPLIERS**



| CCT   | MULTIPLIER |
|-------|------------|
| 2700K | 0.93       |
| 3000K | 1.00       |
| 3500K | 1.07       |
| 4000K | 1.15       |

**Applying Lumen Multipliers to Calculate Delivered Lumens**



| Base Fixture Delivered Lumens (from PHOTOMETRIC DATA) | x | CCT Multiplier | = | Delivered Lumens for Desired Fixture |
|-------------------------------------------------------|---|----------------|---|--------------------------------------|
| <b>STANDARD TRIM Example: TLO020-31 20W 3500K</b>     |   |                |   |                                      |
| 1090 lm                                               | x | 1.07           | = | 1166 lm                              |

**LIGHT DISTRIBUTION**



**3000K 20W**





**3000K 20W**





**3000K 25W**



**3000K 25W**



**3000K 30W**



**ENCORE INTERNATIONAL COMPANY LIMITED**

HK HQ: Room 1, 16/F, Empress Plaza 17-19 Chatham Road South Tsim Sha Tsui, KL.  
 Factory: 2/F, Bld 8th, Zhengzhong Industrial Park, Qiaotou Community, Fuyong, Bao'an District, Shenzhen.

E: sales@encore-tech.com  
 T: +852 6768 2519


**ENCORE**  
 www.encore-tech.com

**DIMENSION**




Track-mounted

TLO020-31  
TLO025-31




Track-mounted

TLO030-31




**INSTALLATION**




Track-mounted




6-pin 3-circuit



DALI






4-pin 3-circuit



Global





Standard



3 pin



Halo



2 pin



Juno



Lightolier

Surface-mounted

TLO020-32  
TLO025-32  
TLO030-32



Pendant

TLO020-33  
TLO025-33  
TLO030-33




Wall-mounted

TLO020-34  
TLO025-34  
TLO030-34



**EXCELLENT MODULAR COMBINATION CONCEPT**



**OVEGA TRACK LIGHT SYSTEM**

UNLIMITED POSSIBILITIES with OVEGA family. Seven versions in excellent modular combination concept with similar appearances but different light solutions entitle OVEGA family will fit smoothly into any retails, museums and galleries environment.

In versions with different light solutions, OVEGA covers high performance accent lighting with very narrow beam 6°, different interchangeable beam lens & different optical accessories, flood lighting of exhibits, beam angle adjusting from narrow to wide, wall washing and projection.

Except versatile light solutions, OVEGA is also a complete family with different installation methods(track-mounted, pendant, surface-mounted and wall-mounted). So, if you have an environment where ask for different light solutions & different installation methods, OVEGA family will be a great choice to get a unified impression.

**DETAILS**



Scan to know more about product information