



Type:


**SPECIFICATION SHEET**

Project:

Page 1 / 6

# DELLA- Pin-Hole

## DM050C



### DESCRIPTION

The DELLA Pin-Hole Downlight features an ultra-narrow concave design that blends seamlessly into the ceiling. Its innovative invisible light optics distribute illumination evenly through multi-surface reflection, delivering wide, comfortable light from a minimal aperture with UGR<6-ideal for premium commercial and residential applications.

### FEATURES

- Ultra-narrow concave design that blends seamlessly into the ceiling.
- It adapts invisible light technology, creating the effect of "seeing the light but not the fixture".
- UGR<6 for ultimate eye comfort.

### SPECIFICATIONS

#### ELECTRICAL

Power:	5W
Voltage:	AC 220-240V
Frequency:	50/60Hz
Power Factor:	>0.90
Dimming:	0/1-10V / TRIAC / DALI

#### OPTICAL

LED Type:	COB
Lumen Output:	256lm
Beam Optic:	Spot (24°, 36°)
Color Quality:	CRI 90+, SDCM≤3
Color Temperature:	Static White: 2700K, 3000K, 3500K, 4000K Tunable White: 2700K-6000K Dim-to Warm: 1800K-3000K

#### LUMINAIRE


Trim Color:	White / Black / Custom Finish*(Consult Factory)
Operating Temperature:	-20°C~35°C
Lifespan:	>50000h@80% (L80)
Warranty:	5 years Carefree for Parts and Components (Labor not included) LED luminarie life reduction and warranty invalidation will occur if installed in environments above 35°C

#### PHYSICAL

Ceiling Thickness:	2mm to 25mm spring plate
Construction:	Aluminum
Mounting:	Recessed with spring plates


**DETAILS**

**Modular Design**



**Pin-Hole**

Small black hole, big light effect — Deep front-focus anti-glare design delivers a UGR < 6 for ultimate comfort. Innovative invisible light emission maximizes overall lighting efficiency.





Type:

Project:

**ORDERING INFORMATION**

<b>DM050C</b>							
<b>MODULE</b>	<b>TRIM</b>	<b>LUMEN</b>	<b>TRIM COLOR</b>	<b>CRI</b>	<b>CCT</b>	<b>OPTIC</b>	<b>DIMMING</b>
<input type="checkbox"/> <b>DM050C</b> DELLA 55mm Aperture (Pin-Hole)	<input type="checkbox"/> <b>DF52RF01N</b> Pin-Hole	<input type="checkbox"/> <b>L02</b> 200lm	<input type="checkbox"/> <b>W</b> White  <input type="checkbox"/> <b>B</b> Black  <input type="checkbox"/> <b>C</b> Custom Finish *(Consult Factory)	<input type="checkbox"/> <b>9</b> 90+	<input type="checkbox"/> <b>27</b> 2700K  <input type="checkbox"/> <b>30</b> 3000K  <input type="checkbox"/> <b>35</b> 3500K  <input type="checkbox"/> <b>40</b> 4000K  <input type="checkbox"/> <b>TW</b> Tunable White 2700K-6000K  <input type="checkbox"/> <b>DW</b> Dim-to Warm 1800K-3000K	<input type="checkbox"/> <b>024</b> Spot 24°  <input type="checkbox"/> <b>036</b> Spot 36°	<input type="checkbox"/> <b>V</b> 0/1-10V  <input type="checkbox"/> <b>T</b> Triac  <input type="checkbox"/> <b>D</b> DALI



Type:

Project:

**PHOTOMETRIC DATA (NON-DIMMING)**

LUMEN PACKAGE	POWER	CCT	24°			36°		
			LUMENS	EFFICACY	MAX CANDELA	LUMENS	EFFICACY	MAX CANDELA
DM050C-DF52RF01N	5W	3000K	201	37	959	256	47	756

Above test data is based on [Pin-Hole \(DF52RF01N\)](#) trim with 3000K 90CRI LED.

**LUMEN MULTIPLIERS**


CCT	MULTIPLIER
2700K	0.95
3000K	1.00
3500K	1.04
4000K	1.06

**Applying Lumen Multipliers to Calculate Delivered Lumens**

Base Fixture Delivered Lumens (from PHOTOMETRIC DATA)	x	CCT Multiplier	=	Delivered Lumens for Desired Fixture
<b>STANDARD TRIM Example: DM050C-DF52RF01N 5W 3500K</b>				
201 lm	x	1.04	=	209 lm





**LIGHT DISTRIBUTION**

**3000K 5W**



Above test data is based on [Pin-Hole \(DF52RF01N\)](#) with 3000K 90CRI LED.

**EXPLODED OVERVIEW - PART SELECTION**



**PARTS**

- A** - Led Module
- B** - Light Source
  - Static White: 2700K, 3000K, 3500K, 4000K
  - Tunable White: 2700K-6000K
  - Dim-to Warm: 1800K-3000K
- C** - LED Holder
- D** - Beam Lens (24° / 36°)
- E** - Fixed Ring
- F** - Pin-Hole Trim For One Light Engine



Type:


Project:

**DIMENSION**

**LED Module**




DM050C



**Trim For Hotel Series**



DM050C-DF52RF01N



Pin-Hole



**DELLA 2.0 DOWNLIGHT SYSTEM**

DELLA, a system of downlights stands out with its exceptional light control technology and anti-glare performance. The system offers multiple sizes ranging from Ø35mm to Ø75mm, with power ratings from 5W to 20W. flexibly adapting to diverse scenarios. Its super modular design enables all optical accessories to be replaced without tools, ensuring smooth operation and a robust structure. Compact, high-efficiency, and evolution-ready design makes DELLA a reliable choice for high-end retail, hospitality, and residential lighting.

DELLA 2.0 is not merely a recessed lighting system; it is our profound interpretation of the relationship between light and space.

**DETAILS**



Scan to know more about product information